





Multi-Grip Blind Rivets

Manufacturer: RivetFast



Materials

Body	Aluminum Alloy
Body	Stainless Steel
Body	Steel
Body	Copper

d	l +0.99	dk	Hole	Min. Grip	Max. Grip	K (k2)	L1	Minimum Tensile Strength (N)	
Φ3.2(+0.09/-0.15)	8	Φ6.0±0.24	Φ3.4	0.5	5.0	1.4 (1.2)	26	670	530
Φ3.2(+0.09/-0.15)	10	Φ6.0±0.24	Φ3.4	2.5	7.0	1.4 (1.2)	26	670	530
Φ3.2(+0.09/-0.15)	12	Φ6.0±0.24	Φ3.4	4.5	9.0	1.4 (1.2)	26	670	530
Φ3.2(+0.09/-0.15)	14	Φ6.0±0.24	Φ3.4	6.5	11.0	1.4 (1.2)	26	670	530
Φ3.2(+0.09/-0.15)	16	Φ6.0±0.24	Φ3.4	8.5	13.0	1.4 (1.2)	26	670	530
Φ4.0(+0.09/-0.15)	10	Φ8.0±0.29	Φ4.2	1.0	6.5	1.7 (1.4)	27	1020	845
Φ4.0(+0.09/-0.15)	12	Φ8.0±0.29	Φ4.2	3.0	8.5	1.7 (1.4)	27	1020	845
Φ4.0(+0.09/-0.15)	14	Φ8.0±0.29	Φ4.2	5.0	10.5	1.7 (1.4)	27	1020	845
Φ4.0(+0.09/-0.15)	16	Φ8.0±0.29	Φ4.2	7.0	12.5	1.7 (1.4)	27	1020	845
Φ4.0(+0.09/-0.15)	18	Φ8.0±0.29	Φ4.2	9.0	14.5	1.7 (1.4)	27	1020	845
Φ4.8(+0.09/-0.15)	10	Φ8.0±0.29	Φ4.1	0.5	5.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	12	Φ8.0±0.29	Φ4.1	2.0	7.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	14	Φ8.0±0.29	Φ4.1	4.0	9.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	16	Φ8.0±0.29	Φ4.1	6.0	11.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	18	Φ8.0±0.29	Φ4.1	8.0	13.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	20	Φ8.0±0.29	Φ4.1	10.0	15.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	22	Φ8.0±0.29	Φ4.1	12.0	17.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	24	Φ8.0±0.29	Φ4.1	14.0	19.0	2 (1.6)	27	1425	1160
Φ4.8(+0.09/-0.15)	26	Φ8.0±0.29	Φ4.1	16.0	21.0	2 (1.6)	27	1425	1160
Φ6.4(+0.11/-0.15)	12	Φ13.0±0.35	Φ6.7	2.0	6.0	2.7 (2.2)	31	7500	13000
Φ6.4(+0.11/-0.15)	16	Φ13.0±0.35	---	6.0	10.0	2.7 (2.2)	31	7500	13000
Φ6.4(+0.11/-0.15)	20	Φ13.0±0.35	Φ6.9	10.0	15.0	2.7 (2.2)	31	7500	13000