





Open-End Blind Rivets

Manufacturer: RivetFast



GB 12618



GB 12617

Materials

Body	Aluminum Alloy
Body	Stainless Steel
Body	Steel
Body	Copper

d	l +0.99	dk	Hole	Min. Grip	Max. Grip	K (k2)	Li	Minimum Tensile Strength (N)				Minimum shear Strength (N)			
								8	10	12	11	8	10	12	11
Φ2.4±0.07	5	Φ4.8±0.24	Φ2.5	0.5	2.5	1 (0.9)	26	258	353	--	--	172	314	--	--
Φ2.4±0.07	7	Φ4.8±0.24	Φ2.5	2.5	4.5	1 (0.9)	26	258	353	--	--	172	314	--	--
Φ2.4±0.07	9	Φ4.8±0.24	Φ2.5	4.5	6.5	1 (0.9)	26	258	353	--	--	172	314	--	--
Φ3.0±0.07	5	Φ6.0±0.24	Φ3.1	0.5	2.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.0±0.07	7	Φ6.0±0.24	Φ3.1	2.0	4.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.0±0.07	9	Φ6.0±0.24	Φ3.1	4.0	6.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.0±0.07	11	Φ6.0±0.24	Φ3.1	6.0	8.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.0±0.07	13	Φ6.0±0.24	Φ3.1	8.0	10.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.0±0.07	15	Φ6.0±0.24	Φ3.1	10.0	12.0	1.4 (1.2)	26	380	595	--	870	300	475	--	680
Φ3.2±0.09	5	Φ6.0±0.24	Φ3.3	0.5	2.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	7	Φ6.0±0.24	Φ3.3	2.0	4.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	9	Φ6.0±0.24	Φ3.3	4.0	6.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	11	Φ6.0±0.24	Φ3.3	6.0	8.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	13	Φ6.0±0.24	Φ3.3	8.0	10.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	15	Φ6.0±0.24	Φ3.3	10.0	12.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ3.2±0.09	17	Φ6.0±0.24	Φ3.3	12.0	14.0	1.4 (1.2)	26	450	670	670	980	360	530	530	760
Φ4.0±0.09	6	Φ8.0±0.29	Φ4.1	2.5	4.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	8	Φ8.0±0.29	Φ4.1	4.5	6.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	10	Φ8.0±0.29	Φ4.1	6.5	8.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	12	Φ8.0±0.29	Φ4.1	8.5	10.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	13	Φ8.0±0.29	Φ4.1	10.5	12.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	16	Φ8.0±0.29	Φ4.1	12.5	14.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	18	Φ8.0±0.29	Φ4.1	14.5	16.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	20	Φ8.0±0.29	Φ4.1	16.5	18.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.0±0.09	22	Φ8.0±0.29	Φ4.1	18.5	20.5	1.7 (1.4)	27	750	1020	1020	1600	540	850	850	1200
Φ4.8±0.09	7	Φ9.5±0.29	Φ4.9	1.0	3.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	9	Φ9.5±0.29	Φ4.9	3.0	5.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	11	Φ9.5±0.29	Φ4.9	5.0	7.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	13	Φ9.5±0.29	Φ4.9	7.0	9.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	15	Φ9.5±0.29	Φ4.9	9.0	11.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	18	Φ9.5±0.29	Φ4.9	11.0	14.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	20	Φ9.5±0.29	Φ4.9	14.0	16.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	22	Φ9.5±0.29	Φ4.9	16.0	18.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	24	Φ9.5±0.29	Φ4.9	18.0	20.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	26	Φ9.5±0.29	Φ4.9	20.0	22.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	28	Φ9.5±0.29	Φ4.9	22.0	24.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ4.8±0.09	30	Φ9.5±0.29	Φ4.9	24.0	26.0	2 (1.6)	27	1050	1425	1425	2230	935	1160	1160	1690
Φ5.0±0.09	7	Φ9.5±0.29	Φ5.1	1.0	3.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	9	Φ9.5±0.29	Φ5.1	3.0	5.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	11	Φ9.5±0.29	Φ5.1	5.0	7.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	13	Φ9.5±0.29	Φ5.1	7.0	9.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	15	Φ9.5±0.29	Φ5.1	9.0	11.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	18	Φ9.5±0.29	Φ5.1	11.0	14.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	20	Φ9.5±0.29	Φ5.1	14.0	16.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	22	Φ9.5±0.29	Φ5.1	16.0	18.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	24	Φ9.5±0.29	Φ5.1	18.0	20.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	26	Φ9.5±0.29	Φ5.1	20.0	22.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	28	Φ9.5±0.29	Φ5.1	22.0	24.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ5.0±0.09	30	Φ9.5±0.29	Φ5.1	24.0	26.0	2 (1.6)	27	1150	1525	1525	2500	990	1280	1280	2000
Φ6.4±0.11	10	Φ12.7±0.35	Φ6.5	1.0	4.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	13	Φ12.7±0.35	Φ6.5	3.0	7.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	15	Φ12.7±0.35	Φ6.5	5.0	9.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	18	Φ12.7±0.35	Φ6.5	8.0	12.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	20	Φ12.7±0.35	Φ6.5	10.0	14.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	22	Φ12.7±0.35	Φ6.5	12.0	16.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	24	Φ12.7±0.35	Φ6.5	14.0	18.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	26	Φ12.7±0.35	Φ6.5	16.0	20.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	28	Φ12.7±0.35	Φ6.5	18.0	22.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	30	Φ12.7±0.35	Φ6.5	20.0	24.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120
Φ6.4±0.11	35	Φ12.7±0.35	Φ6.5	25.0	29.0	2.7 (2.2)	31	2050	2495	2495	4090	1460	2050	2050	3120