





Tri-Fold Blind Rivets

Manufacturer: RivetFast



Materials

Body	Aluminum Alloy
Body	Stainless Steel
Body	Steel

d	$\frac{l}{+0.99}$	dk	Hole	Min. Grip	Max. Grip	K (k2)	L1	Minimum Tensile Strength (N)	Minimum shear Strength (N)
$\Phi 4.0 \pm 0.10$	14.0	$\Phi 8.0 \pm 0.29$	$\Phi 4.2 \sim 4.4$	1.0	3.0	1.7 (1.4)	27	800	500
$\Phi 4.0 \pm 0.10$	18.0	$\Phi 8.0 \pm 0.29$	$\Phi 4.2 \sim 4.4$	3.0	6.5	1.7 (1.4)	27	800	500
$\Phi 4.8 \pm 0.11$	15.5	$\Phi 9.5 \pm 0.29$	$\Phi 5.0 \sim 5.2$	1.0	3.0	2 (1.6)	27	1291	1600
$\Phi 4.8 \pm 0.11$	18.5	$\Phi 9.5 \pm 0.29$	$\Phi 5.0 \sim 5.2$	3.0	6.5	2 (1.6)	27	1291	1600
$\Phi 4.8 \pm 0.11$	21.0	$\Phi 9.5 \pm 0.29$	$\Phi 5.0 \sim 5.2$	3.0	9.5	2 (1.6)	27	1291	1600
$\Phi 4.8 \pm 0.11$	25.0	$\Phi 9.5 \pm 0.29$	$\Phi 5.0 \sim 5.2$	6.5	13.0	2 (1.6)	27	1291	1600